

DESCRIPTION / MODEL	FC-19'	FC-29'	FC-39'	FC-49'	FC-59'	FC-75'
Product Pan						
• Diameter (mm)	482	736	990	1244	1422	1905
• Capacity (liter)	14	35	95	195	426	1150
• Typical Batch Size (kg)	3-7	12-20	40-90	100-180	250-390	450-800
• Drum Speed (r.p.m.)	5-25	2-15	1.5-11	1.5-11	1.5-9	1-7.5
• Pan's Motor (kW)	0.37	0.75	1.5	2.25	3.75	5.5
• Number of Spray Gun	1	1	2	3	4	6
Ventilators						
• System Air flow rate (m ³ /h)	300	800	1400	2500	3500	6000
Motor Capacity						
• Inlet air (kW)	0.37	1.5	1.5	3.7	3.7	5.5
• Outlet air (kW)	1.5	3.75	7.5	11	15	30
Heating and Air						
• Heating Medium	Electrical		Electrical/Steam		Steam	
• Heating Range	Up to + 80° C					
• Max Heating Capacity (kW)	8.1	10.8	22.5	45	-	-
Max Steam						
• Consumption at 2-4 bar (kg/h)	-	-	120	200	280	425
Max Compressed Air						
• Consumption at 4 bar (m ³ /h)	20	30	40	60	80	120
Dimension						
• Width (mm.)	950	1200	1450	1850	2050	2600
• Depth (mm.)	1000	1350	1700	1950	2500	2800
• High (mm.)	1400	1500	1750	2000	2250	2900